

The Burnadette Story...

There was a need for a burner of this size and we responded!

End of story.

IMPORTANT:

The operation of "The Burnadette" incinerator requires proper safety clothing at all times! Safety clothing can be supplied with your order- please enquire. The burning of flammable materials such as used oil, etc. is prohibited. The burning of liquid materials is prohibited.
CSA/Patent Pending

Save Time and Money ... Burnadette Your Waste!

Two sizes to serve you better!

The Original Burnadette is a flyable unit under 1000 lbs. capable of servicing up to a 30 person environment.

Burnadette Two is a larger unit that suits ground transportation capable of servicing a larger environment.

The efficiency of *The Burnadette* takes care of several rubbish related problems associated with the remote location. Bears will be disappointed with good garbage storage practice and/or timely burning of trash; it eliminates the need to use local community dump sites for which there is a problem and growing resistance in many areas; and it eliminates the cost of flying out garbage plus the cost of unnecessary handling of trash, saving you money in not only charter costs but personnel and vehicle transport costs, as well.

For pricing or more information
or to order The Burnadette:
Call **250-847-6069** or
Go online to
www.theburnadette.com

Your Incinerator Solution



**THE
BURNADETTE**
Be kind to the bears!

ORIGINAL BURNADETTE SPECIFICATIONS

- ¼" Plate Steel Construction
- Stainless Steel Grate Construction
- 1 ¼" Fire Brick Lining
- 8" Chimney Opening – 48" High Stack – supplied
- Beckett Industrial Burner – requires 7.1 amps maximum power draw
- Forced Air Injection System – for burn efficiency & temperature
- Top Chamber – door measures 18" x 24" for loading
- Bottom Chamber – door measures 16" x 21" for combustion & clean out
- Upper Burn Chamber – 24" diameter
- Reinforced Upper & Lower Chamber Doors
- Height – 70"
- Footprint – 25" x 25"
- Weight – 750 lb
- Fuel Type: Diesel – No. 1 Stove Oil or No. 2 Furnace Oil
- Max/Min Fuel Consumption – 1 ¼ to 1 ½ US Gal/Hr
- Burn Temperature 175,000 to 420,000 BTU & up to 1800 Degree F
- High Temperature Black Paint
- Auto Fuel Shut Off – after one hour
- 50 lb waste can be burned in less than 10 minutes

Note: The Original Burnadette model does not come with the screen safety guards or the skid and tank options. Both options would be available – call to enquire for cost.



** Both units require ½" wrench for assembly*

** Both units will have motor assembly & stack stored for transport*

Model w/skid and tank not shown



BURNADETTE 2 SPECIFICATIONS

- ¼" Plate Steel Construction
- Stainless Steel Grate Construction
- 2 ¼" Fire Brick Lining
- 8" Chimney Opening - 48" High Stack - supplied
- Beckett Industrial Burner - requires 7.1 amps maximum power draw
- Forced Air Injection System – for burn efficiency & temperature
- Top Chamber – door measures 24' x 24" for loading
- Bottom Chamber – door measures 16" x 26" for combustion & clean out
- Upper Burn Chamber – 30" diameter
- Reinforced Upper & Lower Chamber Doors
- Height – 96"
- Footprint - 36" x 36" / Model With skid & tank – 36" x 6 ½ ft
- Weight - 880 lb / Model with skid & tank -1000 lb
- Screen Safety - guards top of unit
- Fuel Type: Diesel -- No. 1 Stove Oil or No. 2 Furnace Oil
- Max/Min Fuel Consumption – 1 ¼ to 1 ½ US Gal/Hr
- Burn Temperature - 175,000 to 420,000 BTU & up to 1800 degree F
- High Temperature Black Paint
- Auto Fuel Shut off After One Hour
- 75 lb waste can be burned in less than 10 minutes

